



STANDARD

座式用表



ED-305

特色

- 用於學校的電學教學和訓練，工廠、農牧場電力設備的比對和維護
- 高品質的吊線式防震表頭
- 4mm 的多功能極插座
- 刻度板反射鏡設計，降低視差影響
- 橡膠腳墊設計，防止滑動、震動
- 準確度：±1.5%滿刻度
- 刻度長：80 公釐
- 外形尺寸：107(長) × 117(寬) × 53(高)公厘
- 重量：約 300 公克

名稱	規格		編號
交流電流表 (AC Ammeter)	3 檔	1/2.5/5A	305ACA 301
		1/3/5A	305ACA 302
		5/10/25A	305ACA 303
	4 檔	50/250/500/1000mA	305ACA 400
		50/100/250/500mA	305ACA 401
		10mA/50mA/500mA/1A	305ACA 402
		25/100/250/1000mA	305ACA 403
		2/5/10/20A	305ACA 404
5/10/20/30A	305ACA 405		
交流電壓表 (AC Voltmeter)	3 檔	10/30/100V	305ACV 300
		75/150/300V	305ACV 301
	4 檔	1/3/10/30V	305ACV 400
		15/30/150/450V	305ACV 401
		100/250/500/1000V	305ACV 402
		5/30/100/300V	305ACV 403
		75/150/300/750V	305ACV 404
	直流電流表 (DC Ammeter)	1 檔	200mA
500mA			305DCA 101
1A			305DCA 102
3A			305DCA 103
5A			305DCA 104
3 檔		1/3/5A	305DCA 301
		5/10/25A	305DCA 302
4 檔		1/3/10/30mA	305DCA 400
		10/100/300/1000mA	305DCA 401
		10/30/300/1000mA	305DCA 402
		30/100/300/1000mA	305DCA 403
		50/250/500/1000mA	305DCA 404
50mA/500mA/1A/10A	305DCA 405		
直流電壓表 (DC Voltmeter)	3 檔	10/30/100V	305DCV 301
		3/15/300V	305DCV 302
	4 檔	300mV/1V/3V/30V	305DCV 400
		1/3/10/30V	305DCV 401
		10/30/100/300V	305DCV 402
		15/30/150/450V	305DCV 403
		3/30/100/300V	305DCV 404
檢流計 (Galvanometer)	+/- 35G	305G 100	

※特殊規格可另行設計、訂製



STANDARD

BENCH TYPE



ED-305

FEATURES

- Precision meters for plant maintenance, field servicing and educational purposes.
- Taut Band movement with rectifier type.
- Multi terminals (4mm socket) for range selection.
- Carbon pointer, mirror scale to eliminate parallax error.
- High resistance to shock and vibration.
- Accuracy : $\pm 1.5\%$ F.S.
- Scale length : 80mm.
- Dimension : 107(L) \times 117(W) \times 53(D)mm.
- Weight : Approx. 300g.

Name	Range	No.		
AC Ammeter Accuracy : $\pm 1.5\%$ F.S.	3 Ranges	1/2.5/5A	305ACA 301	
		1/3/5A	305ACA 302	
		5/10/25A	305ACA 303	
	4 Ranges	50/250/500/1000mA	305ACA 400	
		50/100/250/500mA	305ACA 401	
		10mA/50mA/500mA/1A	305ACA 402	
		25/100/250/1000mA	305ACA 403	
		2/5/10/20A	305ACA 404	
		5/10/20/30A	305ACA 405	
	AC Voltmeter Accuracy : $\pm 1.5\%$ F.S.	3 Ranges	10/30/100V	305ACV 300
75/150/300V			305ACV 301	
4 Ranges		1/3/10/30V	305ACV 400	
		15/30/150/450V	305ACV 401	
		100/250/500/1000V	305ACV 402	
		5/30/100/300V	305ACV 403	
		75/150/300/750V	305ACV 404	
DC Ammeter Accuracy : $\pm 1.5\%$ F.S.		1 Range	200mA	305DCA 100
			500mA	305DCA 101
	1A		305DCA 102	
	3A		305DCA 103	
	5A		305DCA 104	
	3 Ranges	1/3/5A	305DCA 301	
		5/10/25A	305DCA 302	
	4 Ranges	1/3/10/30mA	305DCA 400	
		10/100/300/1000mA	305DCA 401	
		10/30/300/1000mA	305DCA 402	
		30/100/300/1000mA	305DCA 403	
		50/250/500/1000mA	305DCA 404	
		50mA/500mA/1A/10A	305DCA 405	
	DC Voltmeter Accuracy : $\pm 1.5\%$ F.S.	3 Ranges	10/30/100V	305DCV 301
3/15/300V			305DCV 302	
4 Ranges		300mV/1V/3V/30V	305DCV 400	
		1/3/10/30V	305DCV 401	
		10/30/100/300V	305DCV 402	
		15/30/150/450V	305DCV 403	
		3/30/100/300V	305DCV 404	
DC Galvanometer $\pm 1.5\%$ F.S.	+/- 35G	305G 100		

Special Ranges Are Available Upon Request.