



STANDARD

座式用表



特色

- 用於學校的電學教學和訓練，工廠、農牧場電力設備的比對和維護
- 可以依據實際的需求，選擇不同的規格
- 動圈軸心式表頭
- 簡易防水設計
- 有斜度的盤面，便於識讀
- 4mm 隱藏式的極插座安全設計，也便於測試線的連結
- 攜帶箱式設計，利於使用和儲放
- 準確度：±1.5%滿刻度
- 外型尺寸：245(長)x190(寬)x110(高)公厘
- 重量：約 1300 公克

ED-4195

名稱	規格	
交流電流表 (AC Ammeter)	3 檔	10/30/100mA 1/2.5/5A
	4 檔	50/100/250/500mA 10/50/500mA/1A
交流電壓表 (AC Voltmeter)	3 檔	10/30/100V 75/150/300V
	4 檔	75/150/300/750V
直流電流表 (DC Ammeter)	1 檔	0-1A 0-3A 0-5A 0-200mA 0-500mA
	4 檔	30/100/300/1000uA 30/100/300/1000mA 10/50/500uA/1mA 1/3/10/30mA 1/3/10/300mA
直流電壓表 (DC Voltmeter)	3 檔	3/15/30V 3/15/300V 10/30/100V
	4 檔	1/3/10/30V 10/30/100/300V
檢流計 (Galvanometer)	-35 to + 35	

※特殊規格可以另行設計訂製



STANDARD

BENCH TYPE



FEATURES

- Precision meters for plant maintenance, field servicing and educational purposes.
- Different meters can be chosen from the front panel.
- Moving coil movement.
- Waterproof.
- Tilted front panel for easier viewing.
- Hidden terminals (4mm socket) for range selection and safety design.
- Carbon pointer, mirror scale to eliminate parallax error.
- Accuracy : $\pm 1.5\%$ F.S.
- Dimension : 245(L)x190(W)x110(D)mm.
- Weight : Approx. 1300g.

ED-4195

Name	Range	
AC Ammeter	3 Ranges	10/30/100mA 1/2.5/5A
	4 Ranges	50/100/250/500mA 10/50/500mA/1A
AC Voltmeter	3 Ranges	10/30/100V 75/150/300V
	4 Ranges	75/150/300/750V
DC Ammeter	1 Range	0-1A 0-3A 0-5A 0-200mA 0-500mA
	4 Ranges	30/100/300/1000uA 30/100/300/1000mA 10/50/500uA/1mA 1/3/10/30mA 1/3/10/300mA
DC Voltmeter	3 Ranges	3/15/30V 3/15/300V 10/30/100V
	4 Ranges	1/3/10/30V 10/30/100/300V
Galvanometer	-35 to + 35	

Special Ranges Are Available Upon Request.